

# **L10 Windows Rugged Tablets**

## The ultimate XPAD, XBOOK 2-in-1 and XSLATE 10.1 inch 'go-anywhere' tablets

Put the power of mobile data in the hands of workers in your most demanding environments with Zebra's L10 Windows Rugged Tablet family. Three models meet the needs of workers out in the field in energy, mining, utilities, telecommunications, construction, public safety and government — as well as in warehouses and manufacturing plants. The rugged go-anywhere design is at home indoors, outside, in freezers, sub-zero cold and extreme heat, in forklifts, trucks and other vehicles — and even in bright sunshine. An advanced platform delivers blazing fast performance on all your apps, a battery that provides full shift or around-the-clock power with a single charge, plus the fastest wireless connections — WiFi, Bluetooth, cellular, GPS and NFC. All the right data capture options increase workforce productivity. Customize your L10 tablets with enterprise accessories that simplify everyday use. The L10 Series — the ultimate Windows rugged tablets designed for the workplace.



## The Ultimate in Rugged Versatility

#### Meet the needs of practically any job with three models

The XBOOK L10 2-in-1 rugged tablet offers the ultimate in flexibility — use it as a laptop replacement with the fully-functional keyboard for heavy data entry, remove the keyboard for easy use while standing or walking, or mount in any vehicle with a companion vehicle dock — from forklifts in a warehouse to delivery and first responder vehicles. For workers who spend their day on their feet,

an integrated rigid handle makes the XPAD L10 easy to carry. And the XSLATE L10 is the smallest and lightest model for workers who need a traditional tablet design. No matter which model you choose, you get the same great rugged design, CPU platform, common user experience and consistent support for all of your applications.

## Customize with mix-and-match accessories

No matter what models you choose, you get one enterprise-class accessory family that works with them all. Purchasing and managing accessories is easier. And you can simplify everyday use for your workers with a choice of desktop, industrial and vehicle docks; a carrying case; a shoulder strap; a kickstand and more.

#### Add ports and additional data capture options

Need more ports for easy connection to additional hardware? No problem — just add a True RS232 serial or HDMI-in port. Want to read barcodes to streamline and ensure accurate barcode capture? Add an enterprise-class scanner to the XPAD. Need more security options? Add a Common Access Card (CAC) or Smart Card reader. And if your organization is utilizing RFID, you can add a UHF RFID reader.

## The Ultimate in Reliability and Usability

## A built-to-last rugged design

This waterproof, dustproof and drop-proof tablet is built to handle it all. Drop it on concrete. Get it wet — even if the port covers are open. Use it in extreme heat and subzero cold, inside a truck, car or forklift — or where hazardous materials are present. And the lightweight magnesium frame is stronger than steel and won't twist, so you get durability without adding weight.

#### A large 10.1 in. display with all the right features

Virtually nothing stops users from entering information on the advanced multi-touch display — including gloves, rain and snow. Users can choose their preferred data entry mode, finger or stylus. Corning Gorilla Glass delivers maximum scratch-and-impact resistance to this most vulnerable device component. The ultrabright 1000 nit View Anywhere® display is easy to see, even in direct sunlight.

#### Unmatched battery power — and battery management

Get full shift power with the standard battery and a full 24 hours of power with the extended battery. With a removable hot-swappable battery, your L10 tablets are always in service — never in a charging dock. And with an optional charger, a spare battery is always ready

## The Ultimate in Productivity With Enterprise Data Capture

## Front and rear cameras for double the functionality

Enable video calling with the 2 MP front color camera, allowing your workers to get the instant on-site help they need to resolve technical equipment issues and more. Capture highly detailed photos and videos with the 13 MP color rear camera — ideal for split-second capture of proof-of-condition/delivery/service, evidence capture, incident documentation and more.

## Flawless capture of virtually any barcode in any condition

With the integrated Zebra SE4710 enterprise-class scan engine (optional on XPAD L10 only), workers can capture barcodes as fast as they can press the scan button — even if they are scratched, dirty or poorly printed.

## The Ultimate in Connectivity

## The fastest cellular connections

With support for 4G LTE, your workers are connected all around the world, in urban and remote areas — in vehicles or on foot, indoors and out. And with certification on leading public service networks, including AT&T FirstNet and Verizon, first responders have the reliable connections they need when emergencies overload the commercial networks.

## Longer WiFi range and speed — with less power

2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology allows access points to communicate with multiple devices simultaneously via pinpoint beamforming, boosting WiFi network capacity, speed and range. And processing is shifted from the mobile device to the access point, extending battery cycle time.

## More connectivity options for faster and more flexible communications

Standard Bluetooth 4.2 and support for Gigabit Ethernet, plus options for NFC, GPS and UHF RFID means always being connected.

## The Ultimate in Manageability

#### Easy to secure and manage

All three models are built on a common Windows 10 Pro platform, offering multiple security options. Trusted Platform Module (TPM) 2.0 simplifies the selection and implementation of different levels of security for different users. Support for Smart Card, Common Access Card (CAC) and a fingerprint reader control access to the data and applications on L10 tablets. And a Kensington lock slot protects against theft.

## **Specifications**

| Physical Characteristics |  |
|--------------------------|--|
| Dimensions               | XSLATE: 11.0 in. L x 7.7 in. W x 0.88 in. D<br>280.8 mm L x 195.2 W mm x 22 mm D<br>XPAD: 11.0 in. L x 10.0 in. W x 0.88 in. D<br>280.8 mm L x 255.9 W mm x 22 mm D<br>XBOOK: 11.0 in. L x 8.3 in. W x 2.36 in. D<br>280.8 mm L x 210.8 W mm x 60 mm D   |
| Weight                   | XSLATE: 2.8 lbs/1.3 kg <sup>2</sup><br>XPAD: 3.1 lbs/1.4 kg <sup>2</sup><br>XBOOK: 4.63 lbs/2.1 kg <sup>2</sup>  |
| Frame                    | Magnesium alloy internal frame with external elastomer corner bumpers  |
| Display                  | 10.1 in. 2K resolution display WUXGA 1920 x 1200 (16:10)  - View Anywhere® nominal 1000 Nit capacitive Corning® Gorilla® Glass 3 Capacitive 10-point touch Contrast ratio = 800 to 1000 : 1 Wide viewing angle ±85° Standard user replaceable anti-glare screen protector — 3H hardness User selectable, glove and wet mode Night vision mode supported on Active View Anywhere Display only |
| Graphics                 | Intel® UHD Graphics 505  |
| Battery Life & Power     | Standard battery: up to 9.5 hours <sup>3</sup> Extended battery: up to 25 hours <sup>3</sup> Battery charge time <sup>6</sup> - Standard battery: 2.75 hours with system off <sup>4</sup> - Extended battery: 3.25 hours with system off <sup>4</sup> Standard bridge battery (1 minute swap time) - Hot swap battery feature comes standard Input Voltage: 12-20V, AC Adapter: 19V          |
| Ports/Connectivity       | Docking connector (2) USB 3.0 ports USB Type-C port (USB 2.0, USB 3.0, Display Port out) 3.5 mm audio output (stereo out, mono in) RJ-45 ethernet port Dual Nano SIM (4FF) Micro-SDXC  |
| Expansion Slot           | Micro-SDXC   |
| Integrated Options       | NFC Optional 1D/2D barcode reader (XPAD only) Optional True RS232 serial, or Optional HDMI-In, or Optional CAC / Smart Card reader, or Optional UHF RFID reader (AEI)  |
| Rugged Keyboard          | Included with XBOOK: backlit; IP65; 3.2 ft./1 m droj<br>specification; kick strap/stand (rugged keyboard is<br>optional for the XSLATE and XPAD)   |
| Security                 | Integrated fingerprint reader Trusted Platform Module (TPM) 2.0 Optional CAC / Smart Card reader Kensington cable lock slot TAA compliant  |
| Status Indicators        | System status, battery status, camera active, SSD activity   |
| Audio                    | Intel High Definition audio Realtek® HD Codec RealTek noise cancellation Multi-directional array microphone - 2 microphones (2 front facing array mic) XPAD: 1 front facing speaker XSLATE/XBOOK: 1 rear facing speaker  |

| Operating System          | Windows® 10 Pro 64-bit  |
|---------------------------|---|
| Processor                 | Intel® Pentium® processor N4200; (LPDDR4, 1.10<br>GHz with turbo frequency to 2.50 GHz)   |
| Memory                    | 8 GB  |
| Storage Options           | 128 GB SATA SSD<br>256 GB SATA SSD<br>512 GB SATA SSD   |
| User Environment          |   |
| Operating Temperature     | -4° F to 140° F/-20° C to 60° C; MIL-STD-810G   |
| Storage Temperature       | -22° F to 158° F/-30° C to 70° C; MIL-STD-810G  |
| Thermal Shock             | -22° F to 158° F/-30° C to 70° C within five (5) minutes, non-operating; MIL-STD-810G   |
| Drop Specification        | MIL-STD-810G:<br>6 ft./1.83 m drops to plywood over concrete;<br>4 ft./1.22m drops to concrete  |
| Sealing                   | IP65  |
| Hazardous<br>Environments | C1D2 (Class 1 Division 2) for hazardous locations   |
| Vibration                 | Minimum integrity non-operating, composite who operating; MIL-STD-810G  |
| Shock                     | 40G operating; MIL-STD-810G   |
| Humidity                  | 3% to 95% non-condensing, -22° F to 140° F/-30 to 60°C, 5 cycles of 48Hr; MIL-STD-810G  |
| Water Proofing            | Method 506.5 - Procedure I, wind speed 40 mpl<br>inches per hour, 4 sides; MIL-STD-810G   |
| Blowing Sand              | 20M/S, rate 1.1g/m3 (+/3g) at high temperature 140° F/60° C; MIL-STD-810G   |
| Blowing Dust              | Velocity 8.9M/s dust concentration 3.9 g/m3 at temperature of 140 °F/60° C; MIL-STD-810G  |
| Fluid Contamination       | 50/50 solution of water and bleach, 50/50 solut<br>of water and hydrogen peroxide, diesel fuel,<br>mineral based oil, Lysol disinfectant, denatured<br>alcohol, isopropyl alcohol; MIL-STD-810G   |
| Altitude                  | Operating: 50,000 ft./15,240 m; MIL-STD-810G  |
| Data Capture              |   |
| Camera                    | 13 MP rear camera with AutoFocus; 2 MP front camera with Flash  |
| NFC                       | Optional  |
| RFID                      | Optional UHF RFID Reader (AEI)  |
| Barcode Scanner           | Optional on XPAD only: SE4710 1D/2D imager  |
| Wireless WAN/GPS          | Data (Cellular)   |
| Radio                     | Optional internal wireless (one expansion slot) v choice of:  • Sierra Wireless EM7565, 4G LTE with GNSS (G + GLONASS + Galileo + Beidou)  • Sierra Wireless EM7511, LTE-Advanced with G Discrete GNSS, Navisys u-blox GPS + GLONAS with SBAS |
|                           | AT&T FirstNet Ready & Verizon PNTM certificatio<br>CBRS Capable (Band 48) - EM7511 only   |
| Wireless LAN (WiFi)       |   |
| Radio                     | Intel® Dual Band Wireless-AC 8265 Wi-Fi® plus   |

## Markets and **Applications**

- Warehousing and cold storage
- Telecommunications
- Manufacturing Shop floor
- Oil and Gas
- Mining
- Field service
- Service bay
- Construction
- Utilities
- Government
- Public Safety

| Wireless PAN (Bluetooth) |   |
|--------------------------|---|
| Bluetooth                | Class 1, Bluetooth® 4.2 (EDR + BLE)   |
| Regulatory               |   |
| Product Safety           | UL/CSA 60950-1 2nd Ed.; UL/CSA 62368-1 2nd<br>Ed.; EN 60950-1 2nd Ed.; IEC 62368-1 2nd Ed.; EN<br>62368-1 2nd Ed.; AS/NZS 62368-1; NOM-019-SCFI<br>Hazardous Locations: C1D2; ANSI/ISA 12.12.01-2013  |
| SAR                      | FCC OET 65 Supplement C; CAN/CSA RSS-102<br>Issue 5, Safety Code 6; EN 62311, EN 62209-2;<br>EN62209-2:201  |
| EMC                      | FCC Part 15 B, Class B; CAN/CSA ICES-003, Class<br>B; EN55032, Class B; EN 301-489-1; EN 301-489-17;<br>EN 301-489-24; EN 61000-3-2; EN 61000-3-3;<br>EN55024; EN 303 413   |
| Environment              | California Proposition 65; Battery Charging<br>Systems; RoHS 2 Directive 2011/65/EU; WEEE<br>Directive 2012/19/EU; Battery Waste Directive<br>2013/56/EU; NMX -1-122-NYCE-2006 (Mexico<br>Energy Consumption); Energy Star Compliant;<br>EPEAT Silver |

#### **Accessories**

Vehicle dock; industrial dock; office dock; standard and extended batteries; kickstand with extended battery bracket; single bay battery charger; power adapters; companion keyboard; short and long digitizer and passive pens; combination kickstand and rotating hand strap; soft handle; shoulder strap; carry case; screen protectors; screen cleaning cloth

#### Warranty

Subject to the terms of Zebra's hardware warranty statement, the L10 is warranted against defects in workmanship and materials for a period of 3 (three) years from the date of shipment. For complete warranty statement, go to: http://www.zebra.com/warranty

#### **Recommended Services**

**Zebra OneCare Essential and Select:** Maximize Zebra device availability, device value and operational efficiency with these fully-featured support services that set the industry bar for support.

Zebra Visibility Services — Asset Visibility Services (AVS) and Visibility IQ™ Foresight options on any Zebra OneCare support contract deliver the device management data needed to take device uptime, operational efficiency and return on investment to the next level.

#### **Footnotes**

- 1. Requires a Hazardous Locations certified model. Many XSIate and XPad models are C1D2 certified.
- Weight represents approximate system weight measured with a 36WHr battery. Actual system weight may vary depending on configuration, component and manufacturing variability.
- MobileMark 2014 performance testing software. Battery performance will
  vary by system configuration. Battery life and recharge estimates will vary
  based on system settings, applications, optional features, environmental
  conditions, battery conditioning and user preferences.
- 4. Approximate charging time. Validated charging from 5% to 90% with system on or system off.

Specifications are subject to change without notice.

